

WAVE ID® Plus Mini

A small and capable desktop reader supporting nearly all proximity and contactless credentials worldwide.

The versatile WAVE ID Plus Mini reader combines proximity and contactless technologies into one reader that has the ability to hold four card configurations, enabling growing organizations to seamlessly integrate different ID card technologies. These credential readers are designed for customers seeking to leverage their existing card system for applications beyond building access.

Developed to read virtually any proximity or contactless card type in the world, the WAVE ID Plus Mini is the most powerful, robust reader on the market for identification, authentication, and access applications. Credential-based reader solutions eliminate the need to manually enter user names and passwords, streamlining workflow and eliminating errors for identification.

The WAVE ID Plus Mini reader easily integrates into existing card access systems, allowing companies to leverage the same cards they use to get into the building for countless applications involving logical access to network, software applications, and equipment. Connecting directly into the USB port, the reader emulates keystrokes of the USB model card data on the login screen. Its plug-and-play functionality requires no software for seamless integration with common operating systems and applications.



The small yet powerful credential reader has an extensive feature set that includes:

- Four ID card configurations (2 are pre-set and all four are user definable)
- Auto-tuning for 13.56 MHz antenna to optimize performance in various environments
- User-selectable volume control including a beeper on/off setting
- Support for iCLASS® ID, SE and Seos® (800 models only)
- New compact and modern design
- Articulated cable and rubber feet provide secure desktop placement

WAVE ID® Plus Mini

Standard Features	
Model Series	RDR-80531BKU, WAVE ID Plus Mini Black Keystroke USB Reader RDR-80532BKU, WAVE ID Plus Mini Black SDK USB Reader RDR-80031BKU, WAVE ID Plus Mini w/iCLASS SE & Seos Black Keystroke USB Reader RDR-80032BKU, WAVE ID Plus Mini Black w/iCLASS SE & Seos SDK USB Reader
Operating Frequency	125/132 kHz and 13.56 MHz
Interface	USB
SDK available for writing apps to the reader	Yes

Physical Characteristics	
Dimensions	Length 2.9" (74mm); Width 1.7" (42mm); Height 0.5" (13mm)
Weight	2.5 ounces (72g) with a 6' cable
Housing Color	Black (gray inlay)
Cable Length	6' standard; Contact rf IDEAS for other options
Indicators	LED indicator; Adjustable beeper volume (off, low, medium, high)
Form Factors	Desktop
Power Supply	USB self-powered
Power Consumption	65 mA typical, 185 mA maximum

Environment	
Operating Temperature Range	-13° to 150°F (-25° to 65°C)
Operating Humidity Range	5% to 95% relative humidity, non-condensing
Storage Temperature Range	-40° to 185°F (-40° to 85°C)

Other	
Certifications	FCC-United States; CE Mark-Europe; RCM-Australia; IC-Industry Canada; UL Environmental: RoHS, REACH
Compatible Operating Systems	Windows XP®, 7®, 8®, 10® and Linux (Ubuntu, Red Hat), macOS and Android (keystroking and SDK only)
Configuration Tools	rf IDEAS Configuration Utility and Smartcard Manager Utility, available on rf IDEAS support page
Card Types	Supports nearly all card types worldwide. Visit rfIDEAS.com for full list of supported card types.